

PROFESSIONAL FLOORING PRODUCTS



PRODUCT

GUIDE



EVERYTHING YOU NEED FOR A
SMOOTH INSTALLATION



tilemaster
adhesives

PRIMER & DAMP PROOF MEMBRANE

Primeplus

PRIMING AND BONDING AGENT

- Floor Primer For Absorbent Surfaces
- Designed To Prime, Stabilise & Seal Substrates
- Increases The Adhesion Properties Of Smoothing Compounds
- Prolongs The Working Time Of Smoothing Compounds
- Pigmented For Ease Of Use



Coverage: 3:1 Dilution Rate - 40m² Per Ltr
Drying Time: 15 Minutes
Application Temperature: ≥5°C - ≤30°C
Colour: Green
Pack Sizes: 1 Litre & 5 Litre Bottles



Prime+ Grip

MULTI-PURPOSE BOND ENHANCING PRIMER

- Floor Primer For Non-Absorbent Surfaces
- Designed To Prime & Consolidate Substrates
- Increases The Adhesion Properties Of Smoothing Compounds & Provides "+ Grip" Surface
- Rapid Drying Onto Non-Absorbent Substrates
- Pigmented For Ease Of Use



Coverage: 10m² Per Kg
Drying Time: 15 Minutes
Application Temperature: ≥5°C - ≤30°C
Colour: Blue
Pack Sizes: 1Kg & 5Kg Bottles



FAST One Coat DPM

FAST CURING, ONE COAT, EPOXY, SURFACE DAMP PROOF MEMBRANE

- True One Coat System
- Fast Curing – Ready To Receive Smoothing Compounds In 4 – 5 Hours
- Suitable For Use On Surfaces With A Moisture Reading Of Up To 98% RH
- Can Be Installed Where No Structural DPM Is Present As A One Coat Application.
- Suitable For Use Over Underfloor Heating Systems
- Use On Heated Calcium Sulphate Screeds With A Moisture Reading Of Up To 90% RH
- Use On Unheated Calcium Sulphate Screeds With A Moisture Reading Of Up To 95% RH



Coverage:
When applied to a smooth surface using an A2 trowel - 0.4m²/Kg
3kg - 7.5m²
7kg - 17.5m²
14kg - 35m²
Working Time: 20 Minutes
Cure Time: 4 - 5 hours
Application Temperature: ≥10°C - ≤30°C
Pack Sizes: 3kg, 7kg & 14kg Metal Pails
Colour: Dark Metallic



PREPARATION TOOL

Digital Hygrometer Moisture Tester

SUBSTRATE MOISTURE READER

- Ready To Use
- Easy To Place & Lift
- Digital Readout For Accurate Relative Humidity % Readings
- Suitable For Cement Based & Calcium Sulphate Based Screeds
- Non-Destructive Test Method
- Conforms With BS 8203 Requirements For RH% Readings



SINGLE COMPONENT SMOOTHING COMPOUNDS

LevelFlex+ FINISH

FLEXIBLE, FIBRE REINFORCED, RAPID SETTING SMOOTHING AND LEVELLING COMPOUND

- Superb Surface Finish - Ideal For Resilient Flooring
- Rapid Setting, Walk On After 2.5 Hours
- Lay On After 4 Hours
- Suitable For Use Above Underfloor Heating Systems
- Suitable As A Wearing Surface
- Apply From 2mm - 60mm In One Application
- Moisture Tolerant
- Protein Free
- Pumpable



Water Addition: 4.5 – 5.0 Litres
Coverage: 4.5m² @ 3mm Depth
Working Time: 35 Minutes
Walk On Time: 2.5 Hours
Ready For Covering: 4 Hours
Application Temperature: ≥5°C - ≤30°C
Pack Size: 20Kg
Colour: Grey



FineFlow 3000

EXCEPTIONAL FLOWING & SMOOTHING, HEAVY DUTY SELF LEVELLING FLOOR COMPOUND

- Excellent Levelling & Smoothing Properties
- Apply From 2mm - 20mm
- Walk On After 3 Hours
- Lay On After 24 hours
- Ideal For Underfloor Heating Systems
- Protein Free



Water Addition: 4.4 – 4.8 Litres
Coverage: 4.2m² @ 3mm Depth
Working Time: 20 Minutes
Walk On Time: 3.0 Hours
Ready For Covering: 24 Hours
Application Temperature: ≥5°C - ≤30°C
Pack Size: 20Kg
Colour: Grey



Rapid Level 30

ULTRA-RAPID SETTING, FLEXIBLE, SINGLE COMPONENT SMOOTHING AND LEVELLING COMPOUND

- Lay On After 90 Minutes
- Apply From 2mm - 15mm
- Ultra-Rapid Setting
- Excellent Flow And Self-Smoothing Properties
- Ideal To Encase Electric Underfloor Heating Cables
- Simply Mix With Water
- Protein Free



Water Addition: 4.5 – 5.0 Litres
Coverage: 4.2m² @ 3mm Depth
Working Time: 10 Minutes
Walk On Time: 30 Minutes
Ready For Covering: 90 Minutes
Application Temperature: ≥5°C - ≤30°C
Pack Size: 20Kg
Colour: Beige



DOUBLE COMPONENT SMOOTHING COMPOUNDS

Trade Flow

MULTI-PURPOSE, DOUBLE COMPONENT SMOOTHING AND LEVELLING COMPOUND

- Apply From 2mm - 12mm
- Excellent Flow And Self-Smoothing Properties
- Ideal For Use On Heated Screeds
- Lay On After 12 Hours
- Protein Free
- Low Odour



Liquid Addition:
5Ltr Bottle Of Liquid
Coverage: 5.0m² @ 3mm Depth
Working Time: 20 Minutes
Walk On Time: 2 Hours
Ready For Covering: 12 Hours
Application Temperature:
≥5°C - ≤30°C
Pack Size:
20Kg Bag & 5Ltr Liquid
Colour: Grey



Pro Flow

RAPID SETTING, HIGH PERFORMANCE, FLEXIBLE, DOUBLE COMPONENT SMOOTHING COMPOUND

- Apply From 2mm - 12mm
- Rapid Setting
- Moisture Tolerant - Can Be Used Below A DPM
- Excellent Flow And Self-Smoothing Properties
- Excellent Adhesion Properties Without Priming Most Substrates
- Apply Directly To A DPM Within 24 Hours Without Priming
- Suitable For Use Over Old Adhesive Residues Including Bitumen
- Lay On After 4 Hours
- Protein Free
- Low Odour



Liquid Addition:
5Ltr Bottle Of Liquid
Coverage: 5.0m² @ 3mm Depth
Working Time: 25 Minutes
Walk On Time: 90 Minutes
Ready For Covering: 4 Hours
Application Temperature:
≥5°C - ≤30°C
Pack Size:
20Kg Bag & 5Ltr Liquid
Colour: Grey



Super Flow 30

ULTRA-RAPID SETTING, HIGH PERFORMANCE, FLEXIBLE, DOUBLE COMPONENT SMOOTHING COMPOUND

- Lay On After 90 Minutes
- Apply From 2mm - 15mm
- Ultra-Rapid Setting
- Moisture Tolerant - Can Be Used Below A DPM
- Excellent Flow And Self-Smoothing Properties
- Excellent Adhesion Properties Without Priming Most Substrates
- Apply Directly To A DPM Within 24 Hours Without Priming
- Suitable For Use Over Old Adhesive Residues Including Bitumen
- Protein Free
- Low Odour



Liquid Addition:
4.5Ltr Bottle Of Liquid
Coverage: 4.5m² @ 3mm Depth
Working Time: 10 Minutes
Walk On Time: 30 Minutes
Ready For Covering: 90 Minutes
Application Temperature:
≥5°C - ≤30°C
Pack Size:
20Kg Bag & 4.5Ltr Liquid
Colour: Beige



FLOORING ADHESIVES

Eco-3000 HT

UNIVERSAL HIGH TEMPERATURE FLOORING ADHESIVE

- High Temperature - Ideal For Use Above Underfloor Heating Systems
- Suitable For Installing LVT, PVC, Sheet Vinyl, PVC Backed Carpet
- 40 Minute Working Time
- High Shear Bond Strength
- Hard Final Set
- Solvent Free



YouTube

Working Time: 40 Minutes
Traffic Time: 24 Hours
Coverage: Approximately 50m² – 60m²
Application Temperature: ≥10°C - ≤30°C
Pack Size: 15kg
Colour: Cream



Eco-3000 PS

PRESSURE SENSITIVE FLOORING ADHESIVE

- Pressure Sensitive - Ideal For Design Flooring And Intricate Designs
- Short Open Time
- Install Into After 10 Minutes
- Excellent Initial Grab
- High Bond Strength
- Solvent Free



YouTube

Working Time: 2 Hours
Traffic Time: 24 Hours
Coverage: Approximately 80m² – 90m²
Application Temperature: ≥10°C - ≤30°C
Pack Size: 15kg
Colour: Cream



SUBFLOOR PREPARATION

Rapid Repair Mortar+

RAPID REPAIR MORTAR FOR INTERNAL AND EXTERNAL WALLS AND FLOORS

- Ideal For Repairing, Re-Facing, Filling And Patching
- Ideal For Forming Ramps
- Suitable For Internal And External Use
- Apply From 2mm - 50mm Unfilled, 5mm - 80mm Filled
- Moisture Tolerant - Can Be Used Below A DPM
- Lay On After 90 Minutes
- Slump Free, Ideal For Horizontal And Vertical Applications
- Simply Mix With Water
- Protein Free



Water Addition: 1.9 – 2.2 Litres
Working Time: 10 Minutes
Walk On Time: 30 Minutes
Ready For Covering: 90 Minutes
Application Temperature: ≥5°C - ≤30°C
Pack Size: 11kg
Colour: Grey



Feather

RAPID DRYING PATCH REPAIR AND SMOOTHING COMPOUND

- Apply From Feather Edge Up To 3mm Thick
- Outstanding Bond To Plywood, Smoothing And Levelling Compounds, Concrete, Sand & Cement Screeds And Existing Tiles Without The Need To Prime
- Floor Coverings Can Be Applied In As Little As 15 Minutes After Application
- Suitable For Light And Medium Traffic Areas
- No Additives Required – Simply Mix With Water
- Protein Free



Water Addition: 6.0 Litres
Working Time: 10 Minutes
Walk On Time: 15 Minutes
Ready For Covering: 15 Minutes
Application Temperature: ≥5°C - ≤30°C
Pack Size: 11kg
Colour: Grey



PROFESSIONAL FLOORING PRODUCTS



EVERYTHING YOU NEED FOR A
SMOOTH INSTALLATION

Tilemaster Adhesives Ltd – Kerakoll Group
Tomlinson Road, Leyland, PR25 2DY, United Kingdom

Sales & Technical Support: Tel: **01772 456831**

Email: info@tilemasteradhesives.co.uk

Web: www.tilemasteradhesives.co.uk

